

## Neon Flex

## Product Specification

|                                |                      |
|--------------------------------|----------------------|
| Color type                     | <b>TW</b>            |
| Output color                   | <b>2700,6500</b>     |
| CRI                            | <b>80</b>            |
| Decoding IC                    | -                    |
| LED/ Pixel                     | -                    |
| Control type                   | -                    |
| Voltage (V)                    | <b>24</b>            |
| Power (W/m)                    | <b>16</b>            |
| Efficacy (Lm/W)                | <b>72</b>            |
| Luminous flux (Lm/M)           | <b>1152</b>          |
| Beam angle (°)                 | <b>45</b>            |
| Cutting interval (mm)          | <b>50</b>            |
| Maximum length single feed (m) | <b>5</b>             |
| Maximum length double feed (m) | -                    |
| Width (mm)                     | <b>24</b>            |
| Height (mm)                    | <b>17</b>            |
| Bending radius (mm)            | <b>400</b>           |
| Weight (kg)                    | <b>9.2</b>           |
| Operating temperature (°C)     | <b>-20°C~+50°C</b>   |
| Storage temperature (°C)       | <b>-20°C to 70°C</b> |
| IP rating                      | <b>68</b>            |
| Warranty (year)                | -                    |

## Approvals



## Product information

|                  |                                  |
|------------------|----------------------------------|
| Product category | <b>Neon Flex</b>                 |
| Neonflex type    | <b>3D bending</b>                |
| Product name     | <b>VNL-3D24O-24-45-TW-27K65K</b> |



## Technical drawing