

## Neon Flex

### Product Specification

|                                |                     |
|--------------------------------|---------------------|
| Color type                     | RGB                 |
| Output color                   | Red,Green,Blue,3000 |
| CRI                            | 80                  |
| Decoding IC                    | -                   |
| LED/ Pixel                     | -                   |
| Control type                   | PWM                 |
| Voltage (V)                    | 24                  |
| Power (W/m)                    | 15.3                |
| Efficacy (Lm/W)                | 33.5                |
| Luminous flux (Lm/M)           | 500                 |
| Beam angle (°)                 | 155                 |
| Cutting interval (mm)          | 62.5                |
| Maximum length single feed (m) | 10                  |
| Maximum length double feed (m) | -                   |
| Width (mm)                     | 20                  |
| Height (mm)                    | 18                  |
| Bending radius (mm)            | 120                 |
| Weight (kg)                    | -                   |
| Operating temperature (°C)     | -20~+60             |
| Storage temperature (°C)       | -                   |
| IP rating                      | 67                  |
| Warranty (year)                | 3                   |

### Approvals



### Product information

|                  |                     |
|------------------|---------------------|
| Product category | Neon Flex           |
| Neonflex type    | Frontbending        |
| Product name     | VNL-F20C-24-RGW-30K |



### Technical drawing

